

Lotus



Polypropylene seat and back with
polyurethane foam (optional)
Thickness 2,50 cm
Density 40 kg/m³

Black painted steel 4 legs frame

Polypropylene feet

Dimensions



Weight 12,00 kg
Volume 0,40 cbm (x2pcs)
Guarantee 2 years
Certifications **CERTIFICATION**
16139 - Liv. 1

Optional

Frame



Chromed steel 4
legs frame

Arms



Pair polypropylene
arms



Pair aluminium arms



Pair aluminium arms
with writing table

Colours



BLUE
RAL5003



BLACK
RAL 9005



RED
RAL3000



GREEN
PANT 749SEC



WHITE
RAL9003



GREY
RAL 7012

Fabrics

Bali

CAT. 300
490 gr/ m2
100% POLYPROPYLENE
> 100.000 Martindale
BS 5852 SMALL FLAME

Lord

CAT. 400
390 gr/ m2
100% POLYPROPYLENE
> 100.000 Martindale
BS 5852 - EN 1021-1

King

CAT. 400
290 gr/ m2
100% POLYPROPYLENE TREVIRA CS
> 100.000 Martindale
IIM - C1 - IMO - AM18 - BS 7176

Bond

CAT. 300
250 gr/ m2
100% POLYPROPYLENE
> 150.000 Martindale
IIM - BS 5852 - CRIB 5

FR artificial leather

CAT. 400
550 gr/ m2
85% PVC, 14% PES, 1% PU
> 100.000 Martindale
Classe IIM - BS 5852 - EN 1021

Iron

CAT. 600
715 gr/ m2
88% PVC, 7% POLYPROPYLENE, 4% COTTON, 1% PU
> 200.000 Martindale
IIM - BS 5852 - EN 1021
Antimicrobial Hypoallergenic

Artificial leather

CAT. 300
430 gr/ m2
88% PVC, 12% POLYPROPYLENE
> 100.000 Martindale

Soft

CAT. 400
653 gr/ m2
100% POLYPROPYLENE
> 90.000 Martindale

Use and maintenance

FABRIC

Cleaning: see the maintenance and washing tips in the fabric tab of the color chart.
Use: it is recommended to pay attention to use as it can be torn or cut.

LEATHER

Cleaning: clean with a wet white cloth soaked in water only. Use quality products for cleaning the skin carefully following the instructions of the manufacturer of the cleaning product. In case of doubt, it is advisable to test the product on a part hidden from view to verify the result, waiting at least 24 hours for any problems.
Use: remember that the skin is a delicate material therefore it is recommended to take care during use.

WOOD

Cleaning: Wipe with a damp cloth and soaked in warm water. Always dry after cleaning. Immediately remove any liquid substances or other residues to avoid absorption.
Use: wood surfaces, being a natural material, could, over time, undergo color changes with the use and exposure to light. Remember that wood cannot withstand direct heat sources on the surface.

METAL

Cleaning: both steel or aluminium metal surfaces and painted surfaces must be cleaned with a damp cloth and soaked in hot water. For stubborn stains it is possible to dilute liquid neutral soap in water in moderation. Always dry after cleaning with a soft cloth or deerskin. Do not use creams and pastes to clean steel, do not use chlorine, do not use bleach and other aggressive detergents. Not recommended to use abrasive pastes, scouring pads and abrasive sponges that can scratch metal surfaces.
Use: pay attention to food stains that can leave indelible stains on surfaces.

Disposal and recycling

The product is designed to allow disassembly at the end of its useful life: parts not subject to normal wear, can be reused, recycled or recovered. The disposal must be carried out in the spaces dedicated to this activity.