

# Stella fori




\_\_\_\_\_ Backrest in perforated polypropylene

\_\_\_\_\_ Polypropylene inner seat with polyurethane foam  
 Thickness 3,50 cm  
 Density 25 kg/m<sup>3</sup>

\_\_\_\_\_ Black painted steel oval frame 30x15

\_\_\_\_\_ Polypropylene feet

## Dimensions



<b>Weight</b>	6,00 kg
<b>Volume</b>	0,10 cmb
<b>Guarantee</b>	2 years
<b>Certifications</b>	-

## Optional

### Frame



Chromed steel 4 legs frame



White painted steel 4 legs frame



Grey painted steel 4 legs frame

### Arms



Pair arms



Right arms with writing table



Pair arms with writing table

## Fabrics

### FR fabric

CAT. 200  
380 gr/ m2  
100% POLYPROPYLENE  
> 25.000 Martindale  
IIM - BS 5852 - CRIB 5

### Bali

CAT. 300  
490 gr/ m2  
100% POLYPROPYLENE  
> 100.000 Martindale  
BS 5852 SMALL FLAME

### Lord

CAT. 400  
390 gr/ m2  
100% POLYPROPYLENE  
> 100.000 Martindale  
BS 5852 - EN 1021-1

### Bond

CAT. 300  
250 gr/ m2  
100% POLYPROPYLENE  
> 150.000 Martindale  
IIM - BS 5852 - CRIB 5

### FR artificial leather

CAT. 400  
550 gr/ m2  
85% PVC, 14% PES, 1% PU  
> 100.000 Martindale  
IIM - BS 5852 - EN 1021

### King

CAT. 400  
290 gr/ m2  
100% POLYPROPYLENE TREVIRA CS  
> 100.000 Martindale  
IIM - C1 - IMO - AM18 - BS 7176

### Artificial leather

CAT. 300  
430 gr/ m2  
88% PVC, 12% POLYPROPYLENE  
> 100.000 Martindale

### Soft

CAT. 400  
653 gr/ m2  
100% POLYPROPYLENE  
> 90.000 Martindale

### Iron

CAT. 600  
715 gr/ m2  
88% PVC, 7% POLYPROPYLENE, 4% COTTON, 1% PU  
> 200.000 Martindale  
IIM - BS 5852 - EN 1021  
Antimicrobial Hypoallergenic

## Use and maintenance

### FABRIC

**Cleaning:** see the maintenance and washing tips in the fabric tab of the color chart.  
**Use:** it is recommended to pay attention to use as it can be torn or cut.

### LEATHER

**Cleaning:** clean with a wet white cloth soaked in water only. Use quality products for cleaning the skin carefully following the instructions of the manufacturer of the cleaning product. In case of doubt, it is advisable to test the product on a part hidden from view to verify the result, waiting at least 24 hours for any problems.  
**Use:** remember that the skin is a delicate material therefore it is recommended to take care during use.

### WOOD

**Cleaning:** Wipe with a damp cloth and soaked in warm water. Always dry after cleaning. Immediately remove any liquid substances or other residues to avoid absorption.  
**Use:** wood surfaces, being a natural material, could, over time, undergo color changes with the use and exposure to light. Remember that wood cannot withstand direct heat sources on the surface.

### METAL

**Cleaning:** both steel or aluminium metal surfaces and painted surfaces must be cleaned with a damp cloth and soaked in hot water. For stubborn stains it is possible to dilute liquid neutral soap in water in moderation. Always dry after cleaning with a soft cloth or deerskin. Do not use creams and pastes to clean steel, do not use chlorine, do not use bleach and other aggressive detergents. Not recommended to use abrasive pastes, scouring pads and abrasive sponges that can scratch metal surfaces.  
**Use:** pay attention to food stains that can leave indelible stains on surfaces.

## Disposal and recycling

The product is designed to allow disassembly at the end of its useful life: parts not subject to normal wear, can be reused, recycled or recovered. The disposal must be carried out in the spaces dedicated to this activity.