

Passion



Polypropylene backrest with adjustable lumbar support upholstered in black mesh (coloured mesh in option)

Wooden seat with polyurethane foam
 Thickness 4,50 cm
 Density 30 kg/cbm

4 locking positions synchro mechanism with tension control

Black gas lift H 135

Nylon base d.680 with metal ring

Hard castors d.50

Optional

Castors



Soft castors d.50



Soft castors d.65 (aluminium base)

Bases



Pyramidal chromed steel base d.700



Pyramidal aluminium base d.700

Mechanism



4 locking positions synchro mechanism with seat slide

Headrest



Upholstered headrest adjustable in height and rotation

Arms



Fixed arms TEKNO



Adjustable arms STAR
 1D PP / 1D PU / 2D PU




Adjustable arms FRITZ 1D PP



Adjustable arms MIX 3D

Dimensions



Weight	20,50 kg
Volume	0,35 cbm
Guarantee	2 years
Certifications	OMOLOGAZIONE IIM Bond / FR artificial leather

Fabrics

FR fabric

CAT. 200
380 gr/ m2
100% POLYPROPYLENE
> 25.000 Martindale
IIM - BS 5852 - CRIB 5

Bond

CAT. 300
250 gr/ m2
100% POLYPROPYLENE
> 150.000 Martindale
IIM - BS 5852 - CRIB 5

Artificial leather

CAT. 300
430 gr/ m2
88% PVC, 12% POLYPROPYLENE
> 100.000 Martindale

Bali

CAT. 300
490 gr/ m2
100% POLYPROPYLENE
> 100.000 Martindale
BS 5852 SMALL FLAME

FR artificial leather

CAT. 400
550 gr/ m2
85% PVC, 14% PES, 1% PU
> 100.000 Martindale
IIM - BS 5852 - EN 1021

Soft

CAT. 400
653 gr/ m2
100% POLYPROPYLENE
> 90.000 Martindale

Lord

CAT. 400
390 gr/ m2
100% POLYPROPYLENE
> 100.000 Martindale
BS 5852 - EN 1021-1

King

CAT. 400
290 gr/ m2
100% POLYPROPYLENE TREVIRA CS
> 100.000 Martindale
IIM - C1 - IMO - AM18 - BS 7176

Iron

CAT. 600
715 gr/ m2
88% PVC, 7% POLYPROPYLENE, 4% COTTON, 1% PU
> 200.000 Martindale
IIM - BS 5852 - EN 1021
Antimicrobial Hypoallergenic

Mesh for backrest



Use and maintenance

FABRIC

Cleaning: see the maintenance and washing tips in the fabric tab of the color chart.
Use: it is recommended to pay attention to use as it can be torn or cut.

LEATHER

Cleaning: clean with a wet white cloth soaked in water only. Use quality products for cleaning the skin carefully following the instructions of the manufacturer of the cleaning product. In case of doubt, it is advisable to test the product on a part hidden from view to verify the result, waiting at least 24 hours for any problems.
Use: remember that the skin is a delicate material therefore it is recommended to take care during use.

WOOD

Cleaning: Wipe with a damp cloth and soaked in warm water. Always dry after cleaning. Immediately remove any liquid substances or other residues to avoid absorption.
Use: wood surfaces, being a natural material, could, over time, undergo color changes with the use and exposure to light. Remember that wood cannot withstand direct heat sources on the surface.

METAL

Cleaning: both steel or aluminium metal surfaces and painted surfaces must be cleaned with a damp cloth and soaked in hot water. For stubborn stains it is possible to dilute liquid neutral soap in water in moderation. Always dry after cleaning with a soft cloth or deerskin. Do not use creams and pastes to clean steel, do not use chlorine, do not use bleach and other aggressive detergents. Not recommended to use abrasive pastes, scouring pads and abrasive sponges that can scratch metal surfaces.
Use: pay attention to food stains that can leave indelible stains on surfaces.

Disposal and recycling

The product is designed to allow disassembly at the end of its useful life: parts not subject to normal wear, can be reused, recycled or recovered. The disposal must be carried out in the spaces dedicated to this activity.